Vegaview2.5

bright. brighter. vegaview.



TECHNICAL DATA

Type description	Welding mask with extra bright vie the light state (shade level SL 2.5), colour filter, automatic darkening fi infinite shade level selection from S SL 12, grinding mode operation, inf adjustable delay from 0.1 s to 1.0 s, warning for low battery and grind r	true ilter, SL 8 - ïnite LED
Light transmittance	Ultraviolet-/infrared protection (ma mum at any shade setting)	axi-
	Infinite exterior shade level setting	
	Visible range activated: shade level 8 - 12	
	Visible range not activated: shade level 2.5	
Power supply	2 pcs LI-batteries 3V exchangeable (CR2032)	
Operating time batteries	Approx. 3000 hours (operating)	
Sensors	3 sensors, variable detection angle with movable sensor slider	
Switching time	Light to dark: 0.100 ms at room temperature 0.070 ms at 55°C / 131°F	
	Dark to light: from 0.1 s to 1.0 s adjustable	
Classification	Optical class:	1
	Scattered light:	1
	Homogeneity:	1
	Angular dependence:	2

Shape stability	Welding mask: up to 220°C / 428°F Front cover lens: up to 137°C / 279°F
Protection for ADF	Reflection free front cover lens and inside cover lens
Mask material	PA6.6
Mask colour	Black
Operating temperature	-10°C to +70°C / 14°F to 158°F
Storage temperature	-20°C to +80°C / -4°F to 176°F
Weight	Welding helmet: 482 g, 17.002 oz
Application ranges	Any electric arc welding process Electrode Welding (Stick Welding, SMAW) / MIG / MAG (GMAW) / GMAW High melting rate process / Flux Cored Wire Welding / TIG welding (GTAW) / Plasma Arc Welding / Plasmacutting & Oxy-gas Welding Prohibited for laser welding!
	Grind mode at light state SL 2.5
Scope of delivery	Welding helmet, instruction manual, storage bag, batteries, warranty card and one front cover lense
Standards	CE, ANSI, complies with CSA
Warranty	2 years (except batteries) 1 year warranty extension for online Product registration within the first 6 month. http://register.optrel.com



optrel AG industriestrasse 2 CH-9630 wattwil switzerland www.optrel.com info@optrel.com

